

König Hard Wax PLUS 143 000

Uses

- For the repair of damages like e.g. scratches, peeling-offs, pressure marks and deeper damages.
- For exterior surfaces subject to severe use (e.g. windows and front doors made of wood and plastic, garden furniture etc.) and for the interior (stairways and floors made of wood and laminate).
- For both indoor and outdoor use.

Characteristics

- Mixture of high-quality mineral waxes containing shares of synthetic, coloured with earth and oxide dyes.
- Strong and hard-wearing.
- Heat resistant up to 110°C.
- Good adhesion properties.
- Can be varnished with thin layers of all König-lacquers.
- Colour shades can be mixed together during melting.
- Good elasticity.
- Not to be sanded mechanically.

Application

Remove all loose and splintered particles and indent damage edges. Prior to filling, the substrate should be 'blocked' and be dry. Light-coloured damaged edges should be dyed with König touch-up products according to the colour of the basic shade.

Liquefy Hard Wax PLUS by means of the Hot Knife 439 (medium level) or the Electric Heater 440 (Hard Wax PLUS/Shellac level) and apply in layers to the damaged area. To avoid the formation of bubbles do not process too hot (Hard Wax PLUS to be applied in viscous condition).

Excess filler should be stripped off with the Special Fillers Applicator 161500 (use sharp grooves on the plane surface and round grooves at edges).

To seal the repair and to adjust the gloss level apply Special Repair Lacquer PLUS or Furniture Lacquer PLUS (outdoor!)

Specifications

Softening point:	105-110°C	(ISO 2207)
Dropping point:	115-120°C	(DIN 51801)
Temperature resistance:	shape-retaining from -20°C to +110°C.	
Mechanical stability:	very good.	
Outdoor use:	lightfast and weather-resistant.	
Can be lacquered over:	with all König lacquers.	
Adhesion:	good adhesion to many kinds of plastic, soft and hard woods.	
Shelf life:	unlimited (stored at room temperature, in original unopened container)	

Safety Precautions

- The product is neither subject to the Hazardous Freight Regulations nor to the Dangerous Substances Directive.

Disposal


- No special disposal regulations to be observed. Can be added to the household waste.

Packaging

10 x 8 cm sticks, in cardboard box
20 x 8 cm sticks, in cardboard box
Standard and special colour shades (S.A.)

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG
An der Rosenhelle 5 • D-61138 Niederdorfelden
Phone: 0 61 01- 53 60 0 • Fax: 0 61 01 - 53 60 11
E-mail: info@heinrich-koenig.de

Issue 46/07