

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 1 / 9

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifiers

Article No. (manufacturer/supplier): 220X00  
Identification of the substance or mixture Touch-up Dye  
Art. no. 220000, 220900  
all colours, all gloss values

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Coating(Paint, Varnish).

#### Uses advised against:

Do not use for products which come into contact with the food stuffs.

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

Heinrich König & Co.KG  
An der Rosenhelle 5 Telephone: +49 6101 53600  
D-61138 Niederdorfelden Telefax: +49 6101 5360 11

#### Dept. responsible for information:

laboratory +49 6101 536071  
Only available during office hours: Monday - Thursday 08:00 - 17:00  
Friday 08:00 - 13:30  
E-mail (competent person) SDB@heinrich-koenig.de

### 1.4. Emergency telephone number

Emergency telephone number Emergency CONTACT (24-Hour-Number): GBK  
GmbH +49 (0)6132-84463

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



**Danger**

##### Hazard statements

H225 Highly flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P370 + P378 In case of fire: Use foam to extinguish.  
P501 Dispose of contents/container to industrial incineration plant.

##### contains:

1-methoxy-2-propanol

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 2 / 9

**Supplemental Hazard information (EU)**

n.a.

2.3. **Other hazards**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**3. Composition / Information on ingredients**

3.1. **Substances**

not applicable

3.2. **Mixtures**

**Product description / chemical characterization**

**Description** Dye solution

**Hazardous ingredients**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
203-539-1 107-98-2 603-064-00-3	01-2119457435-35 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	50 - 100
200-578-6 64-17-5 603-002-00-5	01-2119457610-43-0000 ethanol Flam. Liq. 2 H225	20 - 25
285-082-8 85029-57-8	Amines, C10-14-branched and linear alkyl, bis[2,4-dihydro-4-[(2-hydroxy-4-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-) Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	< 0,5
216-455-5 1589-47-5 603-106-00-0	2-methoxypropanol Flam. Liq. 3 H226 / Repr. 1B H360 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318	< 0,5

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

4.1. **Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00  
Print date 27.05.2015  
Version 1.16

Touch-up Dye  
Revision date 12.05.2015  
Issue date 12.05.2015

EN  
Page 3 / 9

## 5. Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Extinguishing media which must not be used for safety reasons:

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 4 / 9

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m<sup>3</sup>; 100 ppm

STEL: 1120 mg/m<sup>3</sup>; 300 ppm

ethanol

INDEX No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

TWA: 1920 mg/m<sup>3</sup>; 1000 ppm

#### Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

#### DNEL:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50,6 mg/kg

DNEL acute inhalative (local), Workers: 553,5 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 369 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 3,3 mg/kg

DNEL long-term dermal (systemic), Consumer: 18,1 mg/kg

DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m<sup>3</sup>

ethanol

INDEX No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

DNEL long-term dermal (systemic), Workers: 343 mg/kg

DNEL acute inhalative (systemic), Workers: 1900 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 950 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 87 mg/kg

DNEL acute dermal, short-term (systemic), Consumer: 950 mg/kg

DNEL long-term dermal (systemic), Consumer: 206 mg/kg

DNEL acute inhalative (systemic), Consumer: 950 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Consumer: 114 mg/m<sup>3</sup>

#### PNEC:

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L

PNEC aquatic, marine water: 1 mg/L

PNEC aquatic, intermittent release: 100 mg/L

PNEC sediment, freshwater: 52,3 mg/kg

PNEC sediment, marine water: 5,2 mg/kg

PNEC, Soil: 4,59 mg/kg

ethanol

INDEX No. 603-002-00-5 / EC No. 200-578-6 / CAS No. 64-17-5

PNEC aquatic, freshwater: 0,96 mg/L

PNEC aquatic, marine water: 0,79 mg/L

PNEC sediment, freshwater: 3,6 mg/kg

PNEC, Soil: 0,63 mg/kg

PNEC sewage treatment plant (STP): 580 mg/L

### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Occupational exposure controls

##### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00  
Print date 27.05.2015  
Version 1.16

Touch-up Dye  
Revision date 12.05.2015  
Issue date 12.05.2015

EN  
Page 5 / 9

(BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.  
Filtering device (full mask or mouthpiece) with filter:AX1

**Hand protection**

For prolonged or repeated handling the following glove material must be used: FKM (fluoro rubber)  
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.  
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374  
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance:**

**Physical state** liquid  
**Colour** characteristic  
**Odour** characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	12 °C	calculated.	
Ignition temperature in °C:	270 °C	calculated.	
Lower explosion limit	1,9 Vol-%	calculated.	
Upper explosion limit	15,0 Vol-%	calculated.	
Vapour pressure at 20 °C:	22,70 mbar	calculated.	
Density at 20 °C:	0,90 g/cm <sup>3</sup>	calculated.	
Vapour density; Bulk density	N.A. kg/m <sup>3</sup>		
Water solubility (g/L)	partially soluble		
pH at 20 °C:	N.A.		
Viscosity at 20 °C	16 s 4 mm	DIN 53211	
Distribution coefficient (n-octanol / water) (log P O/W)	N.A.		
<b>solvent content:</b>			
Organic solvents:	92 Wt %		
Water:	0 Wt %		
Initial boiling point and boiling range	78 °C	calculated.	
Melting point/freezing point	N.A. °C		
Evaporation rate	N.A. °C		
Auto-ignition temperature:	N.A. °C		
Decomposition temperature:	N.A. °C		

**9.2. Other information:**

Explosive properties not explosive.  
Not oxidising.  
Odour threshold: not determined  
No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10. Stability and reactivity**

**10.1. Reactivity**

No known hazardous reactions.

**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

**10.3. Possibility of hazardous reactions**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 6 / 9

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4. Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides. Keine Entstehungsgefahr der oben angeführten Produkte bei sachgemäßem Umgang

**11. Toxicological information**

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]  
No data on preparation itself available.

**11.1. Information on toxicological effects**

**Acute toxicity**

Amines, C10-14-branched and linear alkyl, bis[2,4-dihydro-4-[(2-hydroxy-4-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)

oral, LD50, Rat: > 5000 mg/kg

1-methoxy-2-propanol

oral, LD50, Rat: 4016 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat: 25,8 mg/L (6 h)

ethanol

oral, LD50, Rat: 7060 mg/kg

inhalative (dust and mist), LC50, Rat: 95,6 mg/L (4 h)

**skin corrosion/irritation; Serious eye damage/eye irritation**

2-methoxypropanol

Skin (4 h)

Causes skin irritation.

Eyes

Causes serious eye damage..

**Respiratory or skin sensitisation**

Toxicological data are not available.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

2-methoxypropanol

Reproductive toxicity

May damage the unborn child.

**Specific target organ toxicity**

2-methoxypropanol

Specific target organ toxicity (single exposure), Irritation:

May cause respiratory irritation.

1-methoxy-2-propanol

Specific target organ toxicity (single exposure), drowsiness:

May cause drowsiness or dizziness.

**Aspiration hazard**

Toxicological data are not available.

**Practical experience/human evidence**

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 7 / 9

EC No. CAS No.	Chemical name	Classification according to Regulation (EC) No. 1272/2008 [CLP]
216-455-5 1589-47-5	2-methoxypropanol	Repr. 1B

**Remark**

There is no information available on the preparation itself .

**12. Ecological information**

**overall evaluation**

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

Amines, C10-14-branched and linear alkyl, bis[2,4-dihydro-4-[(2-hydroxy- 4-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)

Fish toxicity, LC50: (96 h)evaluation not determined

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 0,1 - 1 mg/L (48 h)

1-methoxy-2-propanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 6812 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 21100 - 25900 mg/L (48 h)

Immobilisation

ethanol

Fish toxicity, LC50, Leuciscus idus (golden orfe): 8140 mg/L (96 h)

Daphnia toxicity, EC50, Scenedesmus quadricauda: 9000 - 15000 mg/L (48 h)

Bacteria toxicity, Pseudomonas putida: 6500 mg/L (16 h)

**Long-term Ecotoxicity**

Amines, C10-14-branched and linear alkyl, bis[2,4-dihydro-4-[(2-hydroxy- 4-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)

Fish toxicity, LC50: (96 h)

No data available

Daphnia toxicity, EC50: 0,1 (48 h)

No data available

Activated sludge, EC20: > 1000 mg/L

Method: ISO 8192

Technically correct releases of minimal concentrations to adapted biological sewage plants, will not disturb the biodegradability of activated sludge.

1-methoxy-2-propanol

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: > 1000 mg/L (168 h)

**12.2. Persistence and degradability**

Amines, C10-14-branched and linear alkyl, bis[2,4-dihydro-4-[(2-hydroxy- 4-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)

:

In accordance with the required stability the product is poorly biodegradable.

**12.3. Bioaccumulative potential**

Amines, C10-14-branched and linear alkyl, bis[2,4-dihydro-4-[(2-hydroxy- 4-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]chromate(1-)

Distribution coefficient (n-octanol / water) (log P O/W):

No data available

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No data available

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 8 / 9

### 13. Disposal considerations

#### 13.1. Waste treatment methods

##### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

##### List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

##### packaging

##### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

### 14. Transport information

#### 14.1. UN number

1263

#### 14.2. UN proper shipping name

Land transport (ADR/RID): Paint  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

II

#### 14.5. Environmental hazards

Land transport (ADR/RID) n.a.  
Marine pollutant n.a.

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

##### Additional information

##### Land transport (ADR/RID)

tunnel restriction code D/E  
SPECIAL PROVISIONS 640D

##### Sea transport (IMDG)

EmS-No. F-E, S-E

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

### 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 828,929  
VOC-value (in g/L) ASTM D 2369: 828,929

##### National regulations

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

##### Other regulations, restrictions and prohibition regulations



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 220X00 Touch-up Dye  
Print date 27.05.2015 Revision date 12.05.2015  
Version 1.16 Issue date 12.05.2015

EN  
Page 9 / 9

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this preparation were not carried out.

**16. Other information**

**Full text of classification in section 3:**

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic life.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Repr. 1B / H360	Reproductive toxicity	May damage the unborn child.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.

**Additional information**

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.