

König Touch-Up Dye 220 000

Uses

- For the glazing, transparent touch-up by brush for fine grain patterns.
- For redyeing with a cloth ball.
- For patinating with the spray gun.
- For dyeing from light to dark.
- To refill the Felt Touch-Up Dye Pen 210.
- To tone down Colour Touch-Up 240 and all König lacquers, matt finishes and polishes.
- To dye Rex Lith both transparent 151 and wood 152 as well as the Polyester Filling Lacquer 641.
- Recommended for indoor use, only.

Characteristics

- A fast-drying transparent glaze.
- Colour-intensive, can not only be mixed among each other but also with other König-products.
- Limited use on waxed and oiled surfaces.
- Dye application resists wiping and water. Use Liquid Sandpaper 711 to remove.
- Not to be applied to untreated surfaces.

Application

Slightly roughen damage area with Wire Wool or fine Sanding Paper and ensure area is free from dust and grease.

Use the König brush to take up Touch-Up Dye, strike off excess and redye or imitate grain pattern by means of several thin brush strokes. Do not soak area! After drying adjust transitions by means of Wire Wool 413.

When redyeing take up Touch-Up Dye with the cloth ball, spread it on the Mixing Palette 609 and slightly wipe stroke by stroke on surface.

Adjust transitions by slightly wiping with Wire Wool 413 following the grain pattern.

Touch-Up Dye always to be sealed either by Furniture Lacquer PLUS 342-347, Special Repair Lacquer PLUS 336-340 or AQUA Clear Lacquer A342-A346 (protection and gloss sheen adjustment).

Specifications

- Dust-dry:** after a few seconds.
Water resistance: very good.
Adhesion: very good (except to PE/PP), limited adhesion to powder-lacquered surfaces.
- Can be lacquered over:** with any König lacquer.
Shelf life: at least 2 years
(stored upright at room temperature, in original unopened container)

Safety Precautions

- Highly flammable.
- Keep away from sources of ignition. – No smoking.
- Do not breathe vapour.
- Use in well-ventilated areas, only.
- Keep out of reach of children.

Extract of wordings of the law. For further information please see label and Material Safety Data Sheet.

Disposal


- Do not allow product to enter drains or watercourses.
- Container to be added to the household waste, only when completely emptied and dried-out.
- Material leftovers to be disposed of according to the European Waste Code 080111 – *waste paint and varnish containing organic solvents*.

Packaging

30 ml, 250 ml, 500 ml, 1000 ml
Assortment of 5 and 10 (colours at choice)
Standard and special colour shades (S.A.)

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

Issue 48/04