König Hard Wax 141 000



- For the repair of minor and medium-severe damage on a flat surface or on an edge.
- To be used on surfaces that are subject to mediumsevere use.
- For solid wood, veneer, foil, thermosetting, thermoplastic and plastic surfaces for interior use.
- Recommended for indoor use.

Specifications

Softening point: 76°C (ISO 2207) Dropping point: 81 °C (DIN 51801)

Mechanical stability: good.

Can be lacquered over: with all König lacquers. Adhesion:

good adhesion to all plastics,

soft and hard woods.

Shelf life: unlimited

> (stored at room temperature, in original unopened container)

Characteristics

- Mixture of mineral waxes, coloured with earth and oxide dyes.
- Good adhesion properties.
- Colour shades can be mixed together during melting.
- Can be stripped off easily by means of the Special Fillers Applicator, a chisel or the Metal Planer.
- Good elasticity (no development of cracks).

Safety Precautions

The product is neither subject to the Hazardous Freight Regulations nor to the Dangerous Substances Directive.

Disposal

No special disposal regulations to be observed. Can be added to the household waste.

Packaging

20 x 8 cm sticks, in cardboard box 10 x 8 cm sticks, in cardboard box Standard and special colour shades (S.A.)

Application

Remove all loose and splintered particles and indent damage edges with a sharp chisel or the tip of the Metal Planer 406. Use König Touch-Up products to colour damaged edges that are lighter than the base colour.

Use the hot tip of the Electric Heater 440 or the Hot Knife 439 to melt off small quantities of Hard Wax and fill into the damage area.

Important: Do not set the temperature of the heater too high. Surplus filler to be planed off before wax cools down completely, using the Special Fillers Applicator 161500 (sharp grooves on a flat surface, round grooves at edges).

Surplus wax to be wiped off rapidly with the Scotch Brite 609, grain 1500, using light pressure.

Restore grain with König Touch-Up material. The grain pattern can be restored by slightly scratching (e.g. with an upholstery needle).

Finally, apply Special Repair Lacquer PLUS 336-340 to seal and to protect the damage area from dust, dirt and to adjust the gloss sheen, if necessary.

> Further information and Material Safety Data Sheet on the internet at www.heinrich-koenig.de

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden Phone: 0 61 01 - 53 60 0 • Fax: 0 61 01 - 53 60 11

E-mail: info@heinrich-koenig.de

Issue 46/07

