

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
Print date 27.05.2015 Revision date 27.05.2015
Version 1.9 Issue date 12.05.2015

EN
Page 1 / 8

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 319000
Identification of the substance or mixture Moisture and Bloom Eliminator

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Product for surface repair and surface polish.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Heinrich König & Co.KG
An der Rosenhelle 5 Telephone: +49 6101 53600
D-61138 Niederdorfelden Telefax: +49 6101 5360 11

Dept. responsible for information:

laboratory +49 6101 536071
Only available during office hours: Monday - Thursday 08:00 - 17:00
Friday 08:00 - 13:30

E-mail (competent person) SDB@heinrich-koenig.de

1.4. Emergency telephone number

Emergency telephone number Emergency CONTACT (24-Hour-Number): GBK
GmbH +49 (0)6132-84463

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Aerosol 1 / H222	Aerosol	Extremely flammable aerosol.
Aerosol 1 / H229	Aerosol	Pressurised container: May burst if heated.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to industrial incineration plant.

contains:

1-methoxy-2-propanol

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
Print date 27.05.2015 Revision date 27.05.2015
Version 1.9 Issue date 12.05.2015

EN
Page 2 / 8

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

3. Composition / Information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Product description / chemical characterization

Description Aerosol

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification:	Wt % Remark
204-065-8 115-10-6 603-019-00-8	01-2119472128-37-0002 dimethylether compressed gas H280 / Flam. Gas 1 H220	25 - 50
203-539-1 107-98-2 603-064-00-3	01-2119457435-35 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	20 - 25
204-658-1 123-86-4 607-025-00-1	01-2119485493-29-0000 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	20 - 25
201-159-0 78-93-3 606-002-00-3	01-2119457290-43-0000 butanone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	2,5 - 5

Additional information

* Substance with a common (EC) occupational exposure limit value.
Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
Print date 27.05.2015 Revision date 27.05.2015
Version 1.9 Issue date 12.05.2015

EN
Page 3 / 8

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

6. Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

7. Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Occupational exposure limit values:

butanone

INDEX No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
Print date 27.05.2015 Revision date 27.05.2015
Version 1.9 Issue date 12.05.2015

EN
Page 4 / 8

TWA: 600 mg/m³; 200 ppm
STEL: 899 mg/m³; 300 ppm

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

TWA: 375 mg/m³; 100 ppm
STEL: 1120 mg/m³; 300 ppm

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TWA: 724 mg/m³; 150 ppm
STEL: 966 mg/m³; 200 ppm

dimethyl ether

INDEX No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

TWA: 766 mg/m³; 400 ppm
STEL: 958 mg/m³; 500 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

dimethyl ether

INDEX No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

DNEL long-term inhalative (systemic), Workers: 1894 mg/m³
DNEL long-term inhalative (systemic), Consumer: 471 mg/m³

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

DNEL long-term dermal (systemic), Workers: 50,6 mg/kg
DNEL acute inhalative (local), Workers: 553,5 mg/m³
DNEL long-term inhalative (systemic), Workers: 369 mg/m³
DNEL long-term oral (repeated), Consumer: 3,3 mg/kg
DNEL long-term dermal (systemic), Consumer: 18,1 mg/kg
DNEL long-term inhalative (systemic), Consumer: 43,9 mg/m³

butanone

INDEX No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL short-term oral (acute), Workers: 600 mg/kg
DNEL long-term dermal (systemic), Workers: 1161 mg/kg
DNEL long-term inhalative (systemic), Workers: 600 mg/m³
DNEL long-term oral (repeated), Consumer: 31 mg/kg
DNEL long-term inhalative (systemic), Consumer: 106 mg/m³

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute inhalative (systemic), Workers: 960 mg/m³
DNEL long-term inhalative (systemic), Workers: 480 mg/m³
DNEL acute inhalative (systemic), Consumer: 859,7 mg/m³
DNEL long-term inhalative (systemic), Consumer: 102,34 mg/m³

PNEC:

dimethyl ether

INDEX No. 603-019-00-8 / EC No. 204-065-8 / CAS No. 115-10-6

PNEC, Soil: 0,045 mg/kg
PNEC sewage treatment plant (STP): 160 mg/L

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

PNEC aquatic, freshwater: 10 mg/L
PNEC aquatic, marine water: 1 mg/L
PNEC aquatic, intermittent release: 100 mg/L
PNEC sediment, freshwater: 52,3 mg/kg
PNEC sediment, marine water: 5,2 mg/kg
PNEC, Soil: 4,59 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
 Print date 27.05.2015 Revision date 27.05.2015
 Version 1.9 Issue date 12.05.2015

EN
 Page 5 / 8

butanone
 INDEX No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3
 PNEC aquatic, freshwater: 55,8 mg/L
 PNEC aquatic, marine water: 55,8 mg/L
 PNEC sediment, freshwater: 285 mg/kg
 PNEC sewage treatment plant (STP): 709 mg/L

n-butyl acetate
 INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4
 PNEC aquatic, freshwater: 0,18 mg/L
 PNEC aquatic, marine water: 0,018 mg/L
 PNEC aquatic, intermittent release: 0,36 mg/L
 PNEC sediment, freshwater: 0,981 mg/kg
 PNEC sediment, marine water: 0,0981 mg/kg
 PNEC, Soil: 0,0903 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Filtering device (full mask or mouthpiece) with filter:AX1

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state Aerosol
Colour characteristic
Odour characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	-41 °C	calculated.	
Ignition temperature in °C:	273 °C	calculated.	
Lower explosion limit	2,0 Vol-%	calculated.	
Upper explosion limit	18,6 Vol-%	calculated.	
Vapour pressure at 20 °C:	3701,11 mbar	calculated.	
Density at 20 °C:	0,77 g/cm ³	calculated.	
Vapour density; Bulk density	N.A. kg/m ³		
Water solubility (g/L)	partially soluble		
pH at 20 °C:	N.A.		
Viscosity at 20 °C	8 s 4 mm	DIN 53211	
Distribution coefficient (n-octanol / water) (log P O/W)	N.A.		

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
Print date 27.05.2015 Revision date 27.05.2015
Version 1.9 Issue date 12.05.2015

EN
Page 6 / 8

solvent content:

Organic solvents:	100 Wt %	
Water:	0 Wt %	
Initial boiling point and boiling range	-25 °C	calculated.
Melting point/freezing point	N.A. °C	
Evaporation rate	N.A. °C	
Auto-ignition temperature:	N.A. °C	
Decomposition temperature:	N.A. °C	

9.2. **Other information:**

Explosive properties not explosive.
Not oxidising.
Odour threshold: not determined
No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10. Stability and reactivity

10.1. **Reactivity**

No known hazardous reactions.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides. Keine Entstehungsgefahr der oben angeführten Produkte bei sachgemäßem Umgang

11. Toxicological information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]
No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

dimethyl ether

oral, LD50, Rat: > 10000 mg/kg

1-methoxy-2-propanol

oral, LD50, Rat: 4016 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat: 25,8 mg/L (6 h)

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

1-methoxy-2-propanol

Specific target organ toxicity (single exposure), drowsiness:

May cause drowsiness or dizziness.

n-butyl acetate

Specific target organ toxicity (single exposure), drowsiness:

May cause drowsiness or dizziness.

Aspiration hazard

Toxicological data are not available.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 319000 Moisture and Bloom Eliminator
Print date 27.05.2015 Revision date 27.05.2015
Version 1.9 Issue date 12.05.2015

EN
Page 8 / 8

Land transport (ADR/RID): AEROSOL, flammable
Sea transport (IMDG): AEROSOLS
Air transport (ICAO-TI / IATA-DGR): AEROSOL, flammable

14.3. Transport hazard class(es)

2.1

14.4. Packing group

n.a.

14.5. Environmental hazards

Land transport (ADR/RID) n.a.
Marine pollutant n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code D

Sea transport (IMDG)

EmS-No. F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 771,100
VOC-value (in g/L) ASTM D 2369: 771,100

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

16. Other information

Full text of classification in section 3:

compressed gas / H280	Gases under pressure	Contains gas under pressure; may explode if heated.
Flam. Gas 1 / H220	Flammable gases	Extremely flammable gas.
Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.

Additional information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.