

UltraGrip Size 500ml

Code: ULTRAGRIP

UltraGrip is technically advanced adhesion promoter that has excellent grip to virtually any substrate, has been tested on the following: All types of plastic, any non-ferrous metal including aluminium & stainless steel, also glass, porcelain and E-coat substrates.

Suitable substrates

Technical Data

Chemical base	
VOC content	727.0 g/l
Coverage	2,0-2,5 m2
Temp. Resistance	

Application Data



Shake aerosol for at least two minutes, after agitator ball is free.



Apply in cross coats from distance of 250mm from object.



Spray 2 light coats allowing a 3 minute flash off in between coats. Allow to dry for 10 -60 minutes.



After use, turn aerosol upside down and empty valve.

Features and benefits

- · Ultimate adhesion
- High film thickness
- · Resistant to silicone wipe

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

