

09830 – GLASS ADHESION PROMOTER

DESCRIPTION

An additive designed to increase the adhesion of lacquers onto glass.

USE

Mixed with products to apply on glass surfaces in the furniture field and objects **only for interior design**.

CHARACTERISTICS

- Good aesthetical aspect
- Easy to apply
- It improves the adhesion on glass, float glass, acid treated and/or sandblasted glass (**considering the glass superficial treatments, its different types and origin, it is necessary to always carry out some preliminary adhesion tests, above all on safety glass, where the complete acceptability of the end user is essential. It is recommended to paint glass on the air side and not on the tin side surface.**)

SUBSTRATE PREPARATION

Degrease with 00617 PLASTIC CLEANER.

APPLICATION

Spraying.

Mixing ratio:

volume and weight

a) Transparent colours

LS947 (29947) 2K PLASTICGRIP-LS943 (29943) 2K PLASTICGRIP WS	900 parts
BC... BRILLIANT COLOR	100 parts
09830 GLASS ADHESION PROMOTER	20 parts
29355 LECHSYS ACRITOP HARDENER	300 parts
00527 PC THINNER	1000 parts

b) Effect colours

LS947 (29947) 2K PLASTICGRIP-LS943 (29943) 2K PLASTICGRIP WS	500 parts
296../298.. TINTERS LECHSYS EFFECT	500 parts
09830 GLASS ADHESION PROMOTER	20 parts
29355 LECHSYS ACRITOP HARDENER	200 parts
00527 PC THINNER	1000 parts

LH943 HYDROPLAST SEMI GLOSSY WS (derived from binder YD943)	800 parts
YD... TINTERS LECHSYS HYDRO EFFECT	200 parts
09830 GLASS ADHESION PROMOTER	20 parts
14016 HYDROPLAST HARDENER	100 parts
00089 DESALTED WATER	150-350 parts

c) Solid colours

	volume	weight
LS170 (29170)-LS172 (29172) EPODUR in LECHSYS colour	1000 ml	1000 g
09830 GLASS ADHESION PROMOTER	20 ml	20 g
29376 LECHSYS EPODUR HARDENER	200 ml	150 g
00516 LECHSYS EPODUR THINNER	200-400 ml	150-300 g

volume and weight

LH943 HYDROPLAST SEMI GLOSSY WS (derived from binder YD943) in colour	1000 parts
09830 GLASS ADHESION PROMOTER	20 parts
14016 HYDROPLAST HARDENER	100 parts
00089 DESALTED WATER	150-350 parts

USE THE MIXTURES BY 4 HOURS AT 20°C.

FOR APPLICATION METHOD AND OTHER INFORMATION SEE RELEVANT TECHNICAL DATA SHEETS.

IMPORTANT

Keep the product hermetically sealed.

Storage stability: 12 months

Avoid contact with water and atmospheric humidity.

Do not apply on components which will be placed in a washing machine nor on objects which will be constantly exposed in humid rooms, such as kitchens and bathrooms.

**TECHNICAL DATA SHEET N° 0544-GB
UPDATED 06/2021**

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.