

33333 - UV PLUS ADDITIVE 333

DESCRIPTION

Liquid additive to add to all 2K enamels and 1K enamels LS157-LS158 from the Lechsys series and to solvent-based 2K finishes and clearcoats to improve the film protection from UV rays.

USE

Add to a maximum of 5% percentage. Its use doesn't alter the aesthetical aspect of the applied product.

CHARACTERISTICS

- It increases UV resistance
- It doesn't alter the aesthetical aspect of the finishes with which this additive has been mixed

APPLICATION

Mixing ratio:

weight and volume

2K Topcoat

1000 parts

33333 UV PLUS ADDITIVE 333

50 parts

NOTES

Add this additive to the topcoat and mix carefully.

Any further addition other than the stated 5% doesn't achieve any measureable improvement in resistance.

Catalyse and thin the end product following the relevant TDS's instructions.

Storage stability: 24 months

TECHNICAL DATA SHEET N° 0677-GB

UPDATED 11/2024

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.